



TECHNICAL DATA

TOTAL ERROR	0.02%
SENSITIVITY	3.0mV/V $\pm$ 0.003mV/V
30 MINUTE CREEP	0.02% FULL SCALE
ZERO BALANCE	1% FULL SCALE
ZERO ERROR FROM TEMP. CHANGE	0.02% FULL SCALE/10°C
SPAN ERROR FROM TEMP. CHANGE	0.02% FULL SCALE/10°C
INPUT RESISTANCE	400 OHM $\pm$ 10 OHM
OUTPUT RESISTANCE	352 OHM $\pm$ 2 OHM
INSULATION RESISTANCE	> 5000 MEGA OHM
OPERATING TEMPERATURE RANGE	-30° TO 70° C
SAFE LOAD LIMIT	150%
LATERAL LOAD LIMIT	200%
EXCITATION VOLTAGE	RECOMMENDED 10V TO 12V MAX. 15V
PROTECTION CLASS	IP67
CONSTRUCTION	STAINLESS STEEL
CABLE LENGTH	5M x 5MM DIA. PVC
CABLE COLOURS	RED            EXCITATION + BLACK        EXCITATION - BLUE         SENSE + YELLOW      SENSE - GREEN        SIGNAL + WHITE        SIGNAL - PURPLE      SHIELD

MODEL	CAPACITY	PART NO.
BLS250	250kg	PS0004301
BLS500	500kg	PS0004302
BLS750	750kg	PS0004303
BLS1000	1000kg	PS0004304
BLS1500	1500kg	PS0004305
BLS2000	2000kg	PS0004306
BLS2500	2500kg	PS0004307

NOTES

- DO NOT CUT SUPPLIED LOAD CELL CABLE, LOOP EXCESS CABLE AND CABLE TIE
- PRIOR TO INSTALLATION READ AND OBSERVE INSTRUCTION MANUAL

<p>TC PROCESS EQUIPMENT COPYRIGHT THRIVE CONSULTING PTY LTD, SYDNEY AUSTRALIA. NO PART OF THIS DRAWING MAYBE REPRODUCED WITHOUT PERMISSION</p>	TITLE BLS STAINLESS STEEL SIX WIRE LOAD CELL GENERAL ARRANGEMENT													
	<table border="1"> <tr> <td>DRAWN</td> <td>RHS</td> <td>19.04.07</td> </tr> <tr> <td>CHECKED</td> <td>RAS</td> <td>19.04.07</td> </tr> <tr> <td>ENG. MGR.</td> <td></td> <td></td> </tr> <tr> <td>APPR'D</td> <td>MAA</td> <td>19.04.07</td> </tr> </table>	DRAWN	RHS	19.04.07	CHECKED	RAS	19.04.07	ENG. MGR.			APPR'D	MAA	19.04.07	
DRAWN	RHS	19.04.07												
CHECKED	RAS	19.04.07												
ENG. MGR.														
APPR'D	MAA	19.04.07												
SCALE 1:1		REVISION 3	A3											